



<p><b>Unique GX Gear COUPLINGS</b> <b>SIZE G420</b></p> <ul style="list-style-type: none"> <li>Curved Teeth for Reduced wear</li> <li>Piloted on Teeth OD for better</li> <li>Dynamic Balance</li> <li>Compact</li> <li>Higher Bore Capacity</li> <li>Higher Ratings.</li> </ul>	<p><b>GENERAL ASSEMBLY DRAWING</b></p>
--	--

**DIMENSIONS AND STANDARD SIZES**

Size	HP/100 RPM	Nom Torque NM	Peak Torque NM	Max Speed RPM	Max Bore RPM	A MM	B Dia MM	C Dia MM	D Dia MM	E MM	G Dia MM	H MM
G115	10	710	1420	10000	42	87	115	85	60	42	3	105
G150	24	1710	3420	7400	55	103	150	106	78	50	3	120
G180	50	3560	5800	5900	70	127	180	132	100	62	3	150
G195	65	4630	7730	5600	80	127	195	145	113	75	5	150
G 210	90	6410	10700	5000	90	165	210	160	126	80	5	180
G 240	150	10685	16400	4300	100	185	240	180	140	90	5	205
G 250	185	13180	21100	4300	110	185	250	192	155	90	5	205
G 290	230	16380	25200	3900	125	226	290	212	170	110	6	238
G 320	428	30500	45750	3500	140	246	320	240	190	120	6	305
G 350	587	41800	62700	3200	165	278	350	270	216	135	8	360
G 390	793	56500	84750	2900	180	318	390	295	240	155	8	385
G 420	1032	73500	116000	2700	200	348	420	325	265	170	8	420

Mass and Inertia MR<sup>2</sup> are at pilot bore. Limited End Float , Extra end Float on request. Dimension H is alignment Clearance.





## Unique GX Gear COUPLINGS

**SIZE G420****ENGINEERING DATA**

Size	Pilot Bore mm	Wt Kg	MR <sup>2</sup> KgM <sup>2</sup>	Max Misalignment Parallel MM	Ang Deg	Axial +-MM	Grease Reqd Kg	Bolt Tightening Torque NM
G115	15	4.0	0.006	1.1	1.5	6	0.06	9
G150	15	8.6	0.019	1.3	1.5	6	0.11	40
G180	20	15.5	0.043	1.7	1.5	6	0.16	70
G195	30	19.0	0.062	1.7	1.5	6	0.20	70
G 210	40	24.5	0.100	2.1	1.5	10	0.30	70
G 240	40	36.0	0.192	2.4	1.5	10	0.45	180
G 250	40	42.0	0.250	2.4	1.5	10	0.50	180
G 290	50	59.0	0.435	3.0	1.5	12	0.56	350
G 320	50	84.0	00.90	4.0	1.5	12	00.9	350
G 350	50	116.0	01.41	4.5	1.5	16	01.6	350
G 390	60	170.0	02.70	5.0	1.5	16	02.1	600
G 420	75	220.0	04.00	5.5	1.5	16	03.0	600

Mass and Inertia MR<sup>2</sup> are at pilot bore. Limited End Float , Extra end Float on request. Dimension H is alignment Clearance.